

## **SELF-DECLARATION**

## IN ACCORDANCE TO BREEAM-NOR

Self-declaration on below product to be in accordance with the requirements to wood flooring/parquet according to BREEAM-NOR's topic HEA 9.

	NEDlit International UAB			
OF THE PRODUCT	WOODlife Flooring			
MENTATION		YES	NO	COMMENTS
IREMENTS	RELEVANT STANDARDS			
The product can be classified as E1	EN 14342:2005	✓		
according to test method EN 717-1:2004	EN 717-1:2004			
The product has an emission test documenting that emissions of TVOC are below 0,2 mg/m²h	NS-EN 15251:2007	✓		
The product has an emission test documenting that emissions of formaldehyde are below 0,05 mg/m²h	NS-EN 15251:2007	<b>√</b>		
The product has an emission test documenting that emissions of ammonia are below 0,03 mg/m²h	NS-EN 15251:2007	✓		
The product has an emission test documenting that emissions of carcinogenic substances (IARC) are below 0,005 mg/m²h	NS-EN 15251:2007	<b>√</b>		
The product has an emission test documenting that odor dissatisfaction is below 15%	NS-EN 15251:2007	✓		
The emission tests in point 2-6 are conducted according to the ISO 16000-series, with emissions being measured after 28 days.	ISO 16000 (ISO 16000- 3, -6, -9, -11)	✓		
The undersigned can confirm the absence of regulated wood preservatives and to be within the minimum levels.	EN 14342:2005	<b>√</b>		
Dlife Flooring BV				
	Position:		Date:	
			1-1-2016	
	REMENTS  The product can be classified as E1 according to test method EN 717-1:2004  The product has an emission test documenting that emissions of TVOC are below 0,2 mg/m²h  The product has an emission test documenting that emissions of formaldehyde are below 0,05 mg/m²h  The product has an emission test documenting that emissions of ammonia are below 0,03 mg/m²h  The product has an emission test documenting that emissions of carcinogenic substances (IARC) are below 0,005 mg/m²h  The product has an emission test documenting that emissions of carcinogenic substances (IARC) are below 0,005 mg/m²h  The product has an emission test documenting that odor dissatisfaction is below 15%  The emission tests in point 2-6 are conducted according to the ISO 16000-series, with emissions being measured after 28 days.  The undersigned can confirm the absence of regulated wood preservatives and to be	REMENTS The product can be classified as E1 according to test method EN 717-1:2004 The product has an emission test documenting that emissions of TVOC are below 0,2 mg/m²h The product has an emission test documenting that emissions of formaldehyde are below 0,05 mg/m²h The product has an emission test documenting that emissions of formaldehyde are below 0,05 mg/m²h The product has an emission test documenting that emissions of ammonia are below 0,03 mg/m²h The product has an emission test documenting that emissions of carcinogenic substances (IARC) are below 0,005 mg/m²h The product has an emission test documenting that odor dissatisfaction is below 15% The emission tests in point 2-6 are conducted according to the ISO 16000- series, with emissions being measured after 28 days. The undersigned can confirm the absence of regulated wood preservatives and to be within the minimum levels.  Position:	REMENTS The product can be classified as E1 according to test method EN 717-1:2004 The product has an emission test documenting that emissions of TVOC are below 0,2 mg/m²h The product has an emission test documenting that emissions of formaldehyde are below 0,05 mg/m²h The product has an emission test documenting that emissions of ammonia are below 0,03 mg/m²h The product has an emission test documenting that emissions of ammonia are below 0,03 mg/m²h The product has an emission test documenting that emissions of carcinogenic substances (IARC) are below 0,005 mg/m²h The product has an emission test documenting that odor dissatisfaction is below 15% The emission tests in point 2-6 are conducted according to the ISO 16000- series, with emissions being measured after 28 days. The undersigned can confirm the absence of regulated wood preservatives and to be within the minimum levels.  Position:	REMENTS The product can be classified as E1 according to test method EN 717-1:2004 The product has an emission test documenting that emissions of TVOC are below 0,2 mg/m²h The product has an emission test documenting that emissions of formaldehyde are below 0,05 mg/m²h The product has an emission test documenting that emissions of ammonia are below 0,03 mg/m²h The product has an emission test documenting that emissions of ammonia are below 0,03 mg/m²h The product has an emission test documenting that emissions of carcinogenic substances (IARC) are below 0,005 mg/m²h The product has an emission test documenting that odor dissatisfaction is below 15% The emission tests in point 2-6 are conducted according to the ISO 16000-series, with emissions being measured after 28 days. The undersigned can confirm the absence of regulated wood preservatives and to be within the minimum levels.  NS-EN 15251:2007  V  SS-EN 15251:2007  V  SS-EN 15251:2007  V  SS-EN 15251:2007  V  Date:  NS-EN 15251:2007  Date: